**Informazioni tecniche:**

Installazione:	Soffitto, Superficie soffitto
Materiale Corpo:	Polycarbonato
Finitura:	Verde RAL 6003
Tipo di diffusore:	Polycarbonato
Tipo lampada:	LED
Classe energetica:	F
Temperatura colore:	2700K
CRI:	>80
LB Factor:	L80B50 - 50.000h
Rischio fotobiologico:	RG1
Potenza assorbita Watt:	5
Lumen:	600
Real Lumen:	362
Alimentazione:	✓ integrata
LED:	AC DIRECT
Classe di isolamento:	⊕ CL.I
Grado di protezione:	IP 65
Resistenza alla rottura:	IK 06 1J xx3
Marchi di Conformità:	CE UK
Dimmerazione	Taglio di fase

Versione GU10: lampadina non inclusa.



Clic Top

LL14801V2

Lombardo.



Immagini di montaggio:



Lombardo S.r.l.

Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it

lombardo.it

The diagram illustrates a lighting fixture mounted at a height of 2,8m. The fixture's footprint on the ground is 0,5m by 0,5m. A color-coded lux distribution is shown on a grid, with a legend indicating the following values:

- 150,00 (Dark Red)
- 50,00 (Red)
- 25,00 (Orange)
- 10,00 (Light Orange)
- 0,00 (White)

clac_top