



Informazioni tecniche:

Installazione:	Terra, Paletto/bollard terra
Materiale Corpo:	Alluminio
Finitura:	Brown Bronze
Trattamento:	Bordo Mare
Tipo di diffusore:	Polycarbonato
Tipo lampada:	LED
Classe energetica:	D
Temperatura colore:	3000K
CRI:	>80
LB Factor:	L80B20 - 50.000h
Step MacAdam:	3
Rischio fotobiologico:	RG1
Potenza assorbita Watt:	5,5
Lumen:	800
Real Lumen:	270
Alimentazione:	✓ integrata
LED:	220-240 V
Interruttore magnetotermico	120-/-192-/ B10 - C10 - B16 - C16
Classe di isolamento:	□ CL.II
Cavo Alimentazione:	0,30 metri H05RN-F 2x1
Grado di protezione:	IP 66
Resistenza alla rottura:	IK 09 10J xx7
Marchi di Conformità:	CE UK

Base di fissaggio inclusa.



Mushu Cap 300

LL16211M3

Lombardo.



Immagini di montaggio:



LUX

- 150,00
- 50,00
- 25,00
- 10,00
- 0,00

0,5m 0,5m 1,5m 0,3m

mushu_cap_300

Figure 10 is a polar plot showing the gamma-ray beam profile. The main plot has a radial axis for flux in cdk/m, ranging from 0 to 279.99. The angular axis represents the gamma angle in degrees, ranging from 30° to 120° on both sides of the 0°/180° axis. The beam profile is shown as a yellow-shaded region, which is asymmetrical and peaks at 180°. An inset in the top left shows a circular heliostat with a diameter of 150mm and a 90-degree angle, with a red line indicating the beam path. Text on the left side of the main plot provides the following data:

- Flux 279.99 lm
- Maximum 279.99 cdk/m
- Position: C=45.50 G=1.00
- Efficiency: 100.00%
- Date: 12-11-2024
- Asymmetrical